

megaSun® 5800

Technical data

	Super	Super Power	Ultra Power
Tubes in canopy and side	24 x 100 W 2 x 80 W	24 x 160 W 2 x 80 W	24 x 160 W 2 x 80 W
Tubes in bed	18 x 100 W	18 x 100 W	18 x 160 W
Facial tanner	4 x 400 W	4 x 500 W	4 x 500 W
Shoulder tanner (optional)		2 x 250 W	
Nominal power (With air conditioning)	8850 W (10110 W)	10810 W (12070 W)	11890 W (13150 W)
Air discharge	Exhaust-air socket: Ø 300 mm - 1600 mm (top) - Minimum height of the room: 1910 mm		
Minimum capacity (exhaust air)	2250m³/h		
Fuses	Automatic fuse K-type with safety cut-out (3-pole) 3 x 20A + RCD	Automatic fuse K-type with safety cut-out (3-pole) 3 x 25A + RCD	Automatic fuse K-type with safety cut-out (3-pole) 3 x 25A + RCD
evoSystem²	standard	standard	standard
p2-pigment tubes	standard	standard	standard
megaVoice	optional	optional	optional
CPI	optional	optional	optional
musicVibration	optional	optional	optional
mp3-sound-box + audio-connection	optional	optional	optional
aquaCool	optional	optional	optional
aroma including cabin breeze	optional	optional	optional
airCon (ACS)	optional	optional	optional
easyCare	optional	optional	optional
wellnessColor	optional	optional	optional
central exhaust air socket			
Extract air hose			
Warm air return circuit	optional	optional	optional
megaTimer			
Unit dimensions (mm) (height x width x depth)	1460 x 2360 x 1260 (closed) 1860 x 2360 x 1260 (opened)		

The rights to technical and design alterations are reserved.