

megaSun® 6800

Technical data

	Super	Super Power	Ultra Power	IntelliSun
Tubes Canopy & Side	24 x 100 W 2 x 80 W	24 x 160 W 2 x 80 W	24 x 160 W 2 x 80 W	18 x 160 W 6 x 80 W
Tubes Bed	20 x 100 W	20 x 120 W	20 x 160 W	20 x 160 W
Facial tanner	4 x 400 W	4 x 500 W	4 x 500 W	4 x 500 W
Shoulder tanner (optional)	2 x 250 W			
Nominal power (With air conditioning)	7200 W (8460 W)	8900 W (10160 W)	9600 W (10860 W)	9600 - 11600 W (10860 - 12860 W)
Air discharge	Exhaust-air socket: Ø 300 mm - 2095 mm (top) - Minimum height of the room: 2400 mm			
Minimum capacity (exhaust air)	2250m³/h			
Fuses	Automatic fuse K-type with safety cut-out (3-pole) 3 x 20A + RCD	Automatic fuse K-type with safety cut-out (3-pole) 3 x 25A + RCD	Automatic fuse K-type with safety cut-out (3-pole) 3 x 25A + RCD	Automatic fuse K-type with safety cut-out (3-pole) 3 x 25A + RCD
evoSystem²	standard	standard	standard	standard
ACS	standard	standard	standard	standard
megaVoice	standard	standard	standard	standard
pureAir	standard	standard	standard	standard
musicVibration	standard	standard	standard	standard
mp3-sound-box + audio-connection	standard	standard	standard	standard
automatic VolumeControl	standard	standard	standard	standard
USB Audio	standard	standard	standard	standard
fourSeasons	standard	standard	standard	standard
electronicPower	standard	standard	standard	X
p2-Pigmentröhre	standard	standard	standard	standard
preSelection	standard	standard	standard	standard
aquaCool	optional	optional	optional	optional
aroma	optional	optional	optional	optional
airCon	optional	optional	optional	optional
easyCare	X	X	X	optional
central exh. air socket				
Extract air hose				
Warm air return circuit	optional	optional	optional	optional
megaTimer				
Dimensions in mm (Height x width x depth)	1534 x 2380 x 1430 (closed) 1942 x 2380 x 1430 (opened)			

The rights to technical and design alterations are reserved.