

# megaSun<sup>®</sup> 6900

## Technical Data

with facial tanners

megaSun 6900	Super	Super Power	Ultra Power
Reflector tubes in canopy in Watt	27 x 100	27 x 160	27 x 160
Reflector tubes in bench in Watt	21 x 100	21 x 120	21 x 160
Lamps in facial area in Watt, adjustable	4 x 400	4 x 500	4 x 500
Shoulder tanner in Watt	2 x 250	2 x 250	2 x 250
Nominal output in Watt (air-conditioning)	8.550 (9.810)	10.990 (12.250)	11.830 (13.090)
3-pole slow-blow fuse protection in amps (air-conditioning)	25	25	25
Exhaust air Ø in mm	300	300	300
Exhaust air in m <sup>3</sup> /h	2.250	2.250	2.250
touchTronic	Standard	Standard	Standard
pureAir	Standard	Standard	Standard
ACS	Standard	Standard	Standard
megaVoice	Standard	Standard	Standard
evoSystem <sup>2</sup>	Standard	Standard	Standard
x-traTan	Standard	Standard	Standard
CPI	Optional	Optional	Optional
easyCare	Optional	Optional	Optional
airCon	Optional	Optional	Optional
aquaCool	Optional	Optional	Optional
wellnessColor	Optional	Optional	Optional
aroma including cabinBreeze	Optional	Optional	Optional
mp3-sound-box	Optional	Optional	Optional
musicVibration	Optional	Optional	Optional
legTanner	Optional	Optional	Optional

Unit dimensions	closed	2.360 mm x 1.350 mm x 1.400 mm (length x width x height)
	open	2.360 mm x 1.350 mm x 1.800 mm (length x width x height)

The rights to technical and design alterations are reserved.